



Technical Data Sheet

D9900 Terrible Tape™ Double-Coated PET

"The Great Tape That's Tearable"

Description

D9900 is a high tack double-sided adhesive with excellent holding power. Ideal for high speed flying splices of paper, film, and foils as well as general bonding.

Features

Aggressive acrylic adhesive provides quick-stick adhesion. Easy to tear to provide easy application. Polyester carrier provides dimensional stability. Superior cold-stick ability, with excellent shear and heat resistance. Reverse wound with adhesive exposed.

Physical Characteristics	Standard Values
Carrier	0.32 mil PET
Adhesive Type	Acrylic
Adhesive Thickness (each side)	3.35 mil – 0.085 mm
180° Peel Adhesion to Stainless Steel	45 oz/in – 12.2 N/25mm
Tape Color	Clear
Liner	White Paper Release
Total Tape Thickness	3.3 mil – 0.084 mm
Holding Power (PSTC-7) 1000g	>24
Readily Available Lengths	36 and 60 yds

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177